


Order No.:

CJUB4-8M-NA
CJUB4-8M-NB
CJUB4-8M-PA
CJUB4-8M-PB
CJUB4-8M-DA
CJUB4-8M-DB


Features

- Special optical design on the product's back cover, providing 360° visible indicator lights.
- Dedicated IC, stable ultra-long detection distance, and strong anti-interference capabilities.
- Uses durable, oil-resistant cables.
- Detection surface made of oil-resistant, corrosion-resistant material, offering strong environmental resistance.

Wiring



Overall dimension



Technical Parameters

General description	
Switch point function	NPN 、PNP、D
Rated operating distance	4mm
Installation	Non-flush mounting
Standard detector	12*12*1t(Q253A)
Reliable measurement distance	0...3.2mm
Rated grade	
Rated voltage	DC10...30V(Including fluctuation (p-p) 10%
Switching frequency	1.0KHz
Hysteresis range	≤ 15% of sensing distance
Repeatability	<3% of detection distance
No load current	<12mA
Voltage drop	NPN/PNP:<2V； DC two-wire<3V
Working current	＜200mA
Leakage current	＜100uA
Circuit protection	Reverse polarity protection, short-circuit protection
Switching state indication	Red LED indicator
Surrounding environment	
Ambient temperature	-25℃...70℃ (No ice or condensation)
Temperature effect	-Within 25 ℃... 70 ℃, within 15% of detection distance at+24 ℃
Ambient humidity	35...95%RH (No condensation)
Influence of voltage	<3%
Mechanical properties	
Wiring	2m standard cable
Shell material	Brass plated with pearl nickel
Sensing surface	PBT
Protection level	IP67
Withstand Voltage	AC 500V , 50/60Hz 1 minute between the whole charging part and the shell
Insulation resistance	≥20 MΩ (DC 500 V with a megohmmeter) between the whole charging part and the shell
Vibration resistance	10～55 Hz, complex amplitude 1.5mm, 2H in X, Y and Z directions
Certification and Standards	
Product certification	CE CCC CQC ISO9001 ISO14001 ISO45001
Unit weight	About 42g

Accessory

Nuts *2, gaskets *2

The datasheet is subject to change without notice. Copyright Cheemi Tech