


Order No.:

CM-TL-W3MC1
CM-TL-W3MC2
CM-TL-W3MB1
CM-TL-W3MB2
CM-TL-W3MD1
CM-TL-W3MD2

Features

- Dedicated circuit, stable detection distance, strong anti-interference
- Use fold-resistant, oil-resistant cables.


Wiring



Accessory

Screw*1set

Overall dimension



Technical Parameters

General description	
Switch point function	NPN, PNP, D
Rated operating distance Sn	3mm
Installation	Non-flush mounting
Standard detector	12*12*1t(Q253A)
Reliable operating distance Sa	0...2.4mm
Rated grade	
Rated voltage U_B	10...30VDC
Switching frequency f	0.7KHz
Hysteresis range	≤ 15% of sensing distance
Repeatability	<3% of detection distance
No load current Io	<12mA
Leakage current Ir	0...100uA
Voltage drop Ud	NPN/PNP:<2.0V;DC < 3.0V
Working current IL	NPN/PNP<200mA;DC < 100mA
Circuit protection	Reverse polarity protection、Short-circuit protection ，surge absorption
Switching state indication	Red LED indicator
Surrounding environment	
Ambient temperature	-25℃...70℃（No icing, no condensation）
Temperature effect	-Within 25 ℃... 70 ℃, within 10% of detection distance at+24 ℃
Ambient humidity	35...95%RH no condensation
Influence of voltage	<3%
Mechanical properties	
Wiring	Standard wire 2m
Shell material	PBT
Sensing surface	PBT
Protection level	IP67
Withstand voltage	500V AC, 50/60Hz 1 minute between the whole charging part and the shell
Insulation resistance	≥20 MΩ (DC 500 V with a megohmmeter) between the whole charging part and the shell.
Vibration resistance	10～55 Hz, complex amplitude 1.5mm, 2H in X, Y and Z directions
Certification and standards	
Certificates	CE CCC CQC ISO9001 ISO14001 ISO45001
Unit Weight	About 32g

The datasheet is subject to change without notice.
Copyright Cheemi Tech