

Order No.:


CJUB4-8M-NAH
CJUB4-8M-NBH
CJUB4-8M-PAH
CJUB4-8M-PBH
CJUB4-8M-DAH
CJUB4-8M-DBH

Features


- Special optical design on the back cover of the product, 360° around the visible indicator light.
- Dedicated IC, stable ultra-long detection distance, strong anti-interference.
- The detection surface is made of oil-resistant and corrosion-resistant materials, with superior environmental resistance.

Wiring


NPN NO (NA)




NPN NC (NB)




PNP NO (PA)




PNP NC (PB)



DC NO (DA)




DC NC (DB)



Accessory

Toothed nut *2

Overall dimension



Technical Parameters

General description	
Switch point function	NPN, PNP, D
Rated operating distance Sn	4mm
Installation	Non-flush mounting
Standard detector	12*12*1t(Q253A)
Reliable operating distance Sa	0...3.2mm
Rated grade	
Rated voltage U_B	DC 10...30VDC (Including fluctuation (p-p) 10%
Switching frequency f	1.0KHz
Hysteresis range	15% of detection distance
Repeatability	<3% of detection distance
No load current Io	<12mA
Voltage drop Ud	NPN/PNP: <2V, DC two wire: <3V
Working current IL	<200mA
Leakage current Ir	< 100uA
Circuit protection	Reverse polarity protection, short-circuit protection
Switch state indication	Red LED indicator
Surrounding environment	
Ambient temperature	-25℃...70℃ (No icing, no condensation)
Temperature effect	-Within 25 ℃... 70 ℃, within 15% of detection distance at+24 ℃
Ambient humidity	35...95%RH(No condensation)
Influence of voltage	<3%
Mechanical properties	
Wiring	Connector
Shell material	Brass plated with nickel pearl
Sensing surface	PBT
Protection level	IP67
Withstand Voltage	AC 500V , 50/60Hz 1 minute between the whole charging part and the shell
Insulation resistance	≥20 MΩ (DC 500 V with a megohmmeter) between the whole charging part and the shell
Vibration resistance	10～55 Hz, complex amplitude 1.5mm, 2H in X, Y and Z directions
Certification and Standards	
Product certification	CE CCC CQC ISO9001 ISO14001 ISO45001
Unit weight	About 18g

The datasheet is subject to change without notice. Copyright Cheemi Tech